


KCM Roller Chains with Attachments

K1-type Attachments

● Order Product Code

KCM40- ALL K1 240 Links 10ft



40-ALLK1T

Chain No.	Attachment		Plate Thickness T	D	Attachment				Average Tensile Strength kN (kgf)	Maximum Allowable Tension kN (kgf)
	Configuration	Type			A	B	C	K		
KCM 40			1.5	3.6	12.7	9.5	7.9	17.4	17.2 (1,750)	2.75 (280)
KCM 50	ALL	K1	2.0	5.2	15.9	12.7	10.3	22.3	27.9 (2,850)	4.41 (450)
	2L									
	3L									
	4L									
KCM 60	4L		2.4	5.2	19.05	15.9	11.9	27.2	39.5 (4,000)	6.28 (640)
KCM 80			3.2	6.8	25.4	19.1	15.9	35.2	68.6 (7,000)	10.69 (1,090)

! * There are no OL for chains with attachments.
Caution

Chain No.	Configuration	Type	Product Code	Applied Approx Weight g per Attachment Location	Approx. Weight kg/m	No. of Links	Standard Issue	No. in Box (Units or Items)
KCM 40	ALL	K1	40-ALLK1T	2.8	0.61	240L	3m	8
	2L		40-2LK1T					
	3L		40-3LK1T					
	4L		40-4LK1T					
	--		40-K1JL					50
KCM 50	ALL	K1	50-ALLK1T	6.2	1.01	192L	3m	5
	2L		50-2LK1T					
	3L		50-3LK1T					
	4L		50-4LK1T					
	--		50-K1JL					25
KCM 60	ALL	K1	60-ALLK1T	12.0	1.49	160L	3m	4
	2L		60-2LK1T					
	3L		60-3LK1T					
	4L		60-4LK1T					
	--		60-K1JL					15
KCM 80	ALL	K1	80-ALLK1T	26.0	2.50	120L	3m	3
	2L		80-2LK1T					
	3L		80-3LK1T					
	4L		80-4LK1T					
	--		80-K1JL					10