




# KCM Stainless Steel Chains

● Order No. Example  
**40-SUS 240 Links**  
**10ft**  
**3m**  
 Chain No. Unit



2POL  
 \* Only No.25

All parts of Stainless Steel Chains are made of SUS304.

Can be used in a high or low temperature environment or places with acid or alkaline chemical corrosion, water, or steam.

Chain No.	Pitch P	Roller Outer Diameter R	Inner Link Inner Width W	Maximum Allowable Tension kN (kgf)	Approx. Weight (kg/m)	Unit			JL & OL			
						Links Quantity	m	No. in Box (Quantity)	¥	¥		No. in Box (Quantity)
										JL	OL	
25-SUS	6.35	★3.30	3.18	0.12 ( 12)	0.14	480L	3	50			100	
35-SUS	9.525	★5.08	4.78	0.26 ( 27)	0.33	320L		20			100	
40-SUS	12.70	7.92	7.95	0.44 ( 45)	0.63	240L		10			100	
50-SUS	15.875	10.16	9.53	0.69 ( 70)	1.04	192L		5			50	
60-SUS	19.05	11.91	12.70	1.03 (105)	1.50	160L		5			25	
80-RPSUS	25.40	15.87	15.88	1.77 (180)	2.62	120L		3			20	
100-RPSUS	31.75	19.05	19.05	2.55 (260)	4.09	96L	1			10		



Order Method

Chain No. Material Unit and Quantity



Postage

Same-day shipping (Unit Only)

\* Products with dimensional cutting are shipped in 3 working days.



Guide

Customers requesting dimensional cutting products should use SUS FITLINK Roller Chains (FT-SUS) on P50 to P64. [Available for No.25 to 80]



Precautions

- \* The D/L/H dimensions are the same as ►► P70 to P71 Standard Roller Chains.
- \* ★ indicates the bushing diameter of bushed chains.
- \* Dimensional cutting products will be charged as a combination of product price with chain cutting fee included.



Use Examples

When used in food machinery, use 3H (direct food contact-safe oil) Bio-Adnil spray certified by NSF International. See P346

