



KCM Stainless Steel Chains

● Order Product Code

KCM40 - SUS 240 Links
10ft

Chain No. Material Unit



2POL
* Only No.25

All parts of Stainless Steel Chains are made of SUS304.

Can be used in a high or low temperature environment or places with acid or alkaline chemical corrosion, water, or steam.

Chain No.	Pitch P	Roller Outer Diameter R	Inner Link Inner Width W	Maximum Allowable Tension kN (kgf)
KCM 25-SUS	6.35	★3.30	3.18	0.12(12)
KCM 35-SUS	9.525	★5.08	4.78	0.26(27)
KCM 40-SUS	12.70	7.92	7.95	0.44(45)
KCM 50-SUS	15.875	10.16	9.53	0.69(70)
KCM 60-SUS	19.05	11.91	12.70	1.03(105)
KCM 80-RPSUS	25.40	15.87	15.88	1.77(180)
KCM 100-RPSUS	31.75	19.05	19.05	2.55(260)

Chain No.	No. of Rows	Pin Type	Product Code	Approx. Weight kg/m	No. of Links	Standard Issue	No. in Box (Units or Items)
KCM25-SUS	1	RP	25-SUST	0.14	480L	3m	50
			25-SUSJL				100
			25-SUSOL				
KCM35-SUS	1	RP	35-SUST	0.33	320L	3m	20
			35-SUSJL				100
			35-SUSOL				
KCM40-SUS	1	RP	40-SUST	0.63	240L	3m	10
			40-SUSJL				100
			40-SUSOL				
KCM50-SUS	1	RP	50-SUST	1.04	192L	3m	5
			50-SUSJL				50
			50-SUSOL				
KCM60-SUS	1	RP	60-SUST	1.50	160L	3m	5
			60-SUSJL				25
			60-SUSOL				
KCM80-RPSUS	1	RP	80-RPSUST	2.62	120L	3m	3
			80-SUSJL				20
			80-SUSOL				
KCM100-RPSUS	1	RP	100-RPSUST	4.09	96L	3m	1
			100-SUSJL				10
			100-SUSOL				



* The D/L/H dimensions are the same as the P.40 to P.43 Standard Roller Chains.
* ★ indicates the bushing diameter of bushed chains.

Caution