


# Idler Sprockets

## Order Product Code


### ID 40C 15 D15

TYPE No. No. of Teeth  
Sprocket No. D



### <KANA Idler Sprocket Features>

1. Double snap rings used  
(No.25C is a one-sided snap ring specification)  
(Can be easily extracted or pressed in without damaging the bearings, convenient for plating or other surface processing.)
2. Snap rings used that do not interfere with stepped shaft



**m** Carbon Structural Steel

**h** No. 35C ~ 80C

High-frequency Hardened Teeth

(Only No. 25C is without High-frequency Hardened Teeth)

TYPE	No.	No. of Teeth	D	Do	Dp	T	BD	BL	Bearing No.	Weight kg
ID	25C	17	6	38	34.558	2.8	27	12	606ZZ	0.05
		19	8	42	38.580		31	13	608ZZ	0.05
		20	10	44	40.592		33	13	6900ZZ	0.06
	35C	16	10	54	48.824	4.3	38	14	6000ZZ	0.11
		18	12	54	48.824		6001ZZ	0.10		
		21	15	60	54.852		44	17	6202ZZ	0.16
		25	17	69	63.908		53	19	6203ZZ	0.24
	40C	13	10	59	53.068	7.2	38	14	6204ZZ	0.33
		15	12	59	53.068		60	21	6204ZZ	0.40
		17	15	67	61.084		44	17	6202ZZ	0.19
		19	17	76	69.116		53	19	6203ZZ	0.30
	50C	12	12	69	61.336	8.7	43	16	6204ZZ	0.49
		13	15	74	66.335		44	17	6202ZZ	0.23
		15	17	84	76.355		53	19	6203ZZ	0.37
		17	20	94	86.395		60	21	6204ZZ	0.49
60C	11	12	76	67.617	11.7	44	16	6201ZZ	0.26	
	13	15	89	79.602		44	17	6202ZZ	0.27	
	14	17	89	79.602		53	19	6203ZZ	0.46	
80C	9	15	85	74.265	14.6	44	17	6204ZZ	0.56	
	10	17	93	82.196		44	17	6202ZZ	0.38	
	11	20	102	90.156		52	19	6203ZZ	0.57	
						60	21	6204ZZ	0.69	



\* The bearing is located in the center of the sprocket.

Caution