



**NEW**

# B-type Double Idler Sprockets



● **Order No. Example**

**WID 40B 15 D15**



The KANA standard B-type W (double) idler sprocket holds tension at the appropriate level during roller chain transmission. When using the B-type drive sprocket and driven sprocket wheel, design can be made easier by using the same B type W idler. This product also has excellent load bearing capacity since it uses two bearings.

- m Carbon Structural Steel
- h High-frequency Hardened Teeth
- s Black Oxide Finish

Type	No.	No. of Teeth	I.D. D	Outer Diameter Do	Pitch Diameter Dp	Tooth Width T	Boss BD	Total Width BL	Bearing Center Z from Boss End Face	Eccentricity X	Used Bearing	Total Bearing Width Y	Weight kg	Idler Pin Applicable Size	ID Adapter Applicable Size	¥
<b>WID</b>	35B	16	10 12	54	48.82	4.3	38	22	11	8.85	6000ZZ 6001ZZ	16	0.14 0.15	IDP6000W IDP6001W	AD6000 AD6001	
		18	15	60	54.85		44	28	14	11.85	6202ZZ	22	0.23	IDP6202W	AD6202	
		21	17	69	63.91		53	31	15.5	13.35	6203ZZ	24	0.32	IDP6203W	AD6203	
		25	20	81	76.00		60	35	17.5	15.35	6204ZZ	28	0.46	IDP6204W	AD6204	
	40B	13	10 12	59	53.07	7.2	38	22	11	7.4	6000ZZ 6001ZZ	16	0.19 0.18	IDP6000W IDP6001W	AD6000 AD6001	
		15	15	67	61.08		44	28	14	10.4	6202ZZ	22	0.27	IDP6202W	AD6202	
		17	17	76	69.12		53	31	15.5	11.9	6203ZZ	24	0.39	IDP6203W	AD6203	
	50B	19	20	84	77.16	8.7	60	35	17.5	13.9	6204ZZ	28	0.59	IDP6204W	AD6204	
		12	12	69	61.34		43	26	13	8.65	6201ZZ	20	0.27	IDP6201W	AD6201	
		13	15	74	66.34		44	28	14	9.65	6202ZZ	22	0.31	IDP6202W	AD6202	
	60B	15	17	84	76.35	11.7	53	31	15.5	11.15	6203ZZ	24	0.46	IDP6203W	AD6203	
		17	20	94	86.39		60	35	17.5	13.15	6204ZZ	28	0.66	IDP6204W	AD6204	
11		12 15	76	67.62	44		26 28	13 14	7.15 8.15	6201ZZ 6202ZZ	20 22	0.35 0.36	IDP6201W IDP6202W	AD6201 AD6202		
80B	13	17	89	79.60	14.6	53	31	15.5	9.65	6203ZZ	24	0.56	IDP6203W	AD6203		
	14	20	95	85.61		60	35	17.5	11.65	6204ZZ	28	0.70	IDP6204W	AD6204		
	9	15	85	74.27		44	28	14	6.7	6202ZZ	22	0.46	IDP6202W	AD6202		
	10	17	93	82.20		53	31	15.5	8.2	6203ZZ	24	0.62	IDP6203W	AD6203		
	11	20	102	90.16		60	35	17.5	10.2	6204ZZ	28	0.80	IDP6204W	AD6204		



Order Method:   and Quantity



Postage: **Same-day shipping**



Precautions: \* The bearing is located in the center of the sprocket.



Guide: \* Since we also manufacture sizes other than those in the catalog upon request, please contact our company's sales office for details.



Use Examples: \* Use the idler pin/ID adapter. P118 and P119 P114

